

## 28 VDC Linear Power Supplies

### Product Features

- **Solid State Electronically-Regulated**
- **Fold-Back Current Limiting**
  - ▶ Protects power supply from excessive current & continuous shorted output
- **Crowbar Over-Voltage Protection**
  - ▶ On all models
- **Maintain Regulation & Low Ripple**
  - ▶ At low line input voltage
- **Heavy-Duty Heat Sink**
  - ▶ Chassis mount fuse
- **Three Conductor Power Cords**
- **One Year Warranty**
- **Made in USA**

### Product Specifications

<b>Input Voltage</b>	105 - 125 VAC
<b>Output Voltage</b>	28 VDC $\pm$ 0.05 Volts (Internally Adjustable: 22-32 VDC)
<b>Ripple</b>	<5mv Peak to Peak (Full load & Low line)

### Model Selection Guide

Model	Continuous Duty (Amps)	ICS (Amps)	Dimensions	Weight (lbs)
<b>LS-3A</b>	3	4	3¾H x 6½W x 9D	9
<b>LS-10A</b>	8	10	5H x 9W x 10½D	18
<b>LS-18A</b>	12	18	5H x 11W x 11D	27
<b>LS-25A</b>	18	25	6H x 13¾W x 11D	46
<b>LS-35A</b>	27	35	6H x 13¾W x 12D	49
<b>LS-35M</b>	27	35	6H x 13¾W x 12D	49



### Model Selection Guide

Model	Continuous Duty (Amps)	ICS (Amps)	Dimensions	Weight (lbs)
<b>LSRM-18A</b>	12	18	5¼H x 19W x 12½D	38
<b>LSRM-25A</b>	18	25	5¼H x 19W x 12½D	50
<b>LSRM-35A</b>	27	35	7H x 19W x 12½D	55
<b>LSRM-18M</b>	12	18	5¼H x 19W x 12½D	38
<b>LSRM-25M</b>	18	25	5¼H x 19W x 12½D	50
<b>LSRM-35M</b>	27	35	7H x 19W x 12½D	55



### Model Selection Guide

Model	Continuous Duty (Amps)			ICS (Amps)	Dimensions	Weight (lbs)
	@28V	@12V	@5V			
<b>VLS-10M</b>	8	4	2	18	5H x 9W x 10½D	20
<b>VLS-25M</b>	18	10	5	25	6H x 13¾W x 11D	46
<b>VLS-35M</b>	27	15	8	35	6H x 13¾W x 12D	49

