

Plug-In 15 & 20 Amp Rackmount Protectors

Bring power safely and conveniently to wherever your need it with a full line of standard and custom **Plug-In Rackmount & Cabinet** Units. These units are ideal for use in a wide variety of settings, including relay racks and cabinets, laboratories, workshops, classrooms and offices.

Plug-In Rackmount & Cabinet units include compact, 90°, deluxe control, industrial, hospital grade, and international units. Most are available in both 15 and 20 Amp configurations.









Product Features





- **User-Ready Units**
 - ▶ Plug-in units provide power distribution in a portable, plug-in unit.
- **Rugged Construction**
 - ▶ Durable 2" x 1¾" (44mm x 51mm) or 3½" x 2" (89mm x 44mm) aluminum housing. Some plug-in units are available with an impact-resistant plastic housing.
- **Space Saving**
 - ▶ Rackmount units fit standard 19" (482mm) relay racks. Compact 1U design takes up minimum space. 23" (584mm) units available.
- **Low Profile**
 - ▶ Cabinet units offer a narrow 1½" x 1 3/16" (38mm x 20mm) aluminum housing.
- **Aesthetically Pleasing**
 - ▶ Rackmount units have a black matte finish and a black cord. Cabinet, compact and industrial units have a grey finish and a black cord. Deluxe control and 20 Amp units have a putty white finish and a black cord. Most units with a putty white finish have a putty white cord. Hospital grade units have a white finish and a white cord.
- **Flexible Mounting**
 - ▶ Each unit features one of four different mounting types. Each mounting method has been designed to optimize the performance of the product. Complete mounting hardware and installation instructions are included with every unit.
- **Cord Properly Rated To Load Requirements**
 - ▶ 15 Amp units have a 14/3 SJT cord and a NEMA 5-15P plug. 20 Amp units have a 12/3 SJT cord and a NEMA 5-20P or NEMA 1%-20P plug.
- **Lighted Switch**
 - ▶ Most units have lighted ON/OFF switches to control power to the unit.
- **Resettable Circuit Breaker**
 - ▶ Provides overload protection
- **Product Warranty**
 - ▶ Two-Year
- **UL Recognized or Listed And CSA Certified**
 - ▶ Rackmount units are UL recognized components. All other units are UL listed and meet UL1363 standards. All 15A units are CSA certified.

Model Selection Guide

15 Amp Rackmount Plug-In Outlets

Model	Description/Specifications	Dimensions
 J08B0B/J08B2B	8 rear outlets, lighted switch. Receptacles rotated 90° and 4 outlets spaced to accommodate transformers.	6' (1.8m) or 15' (4.6m) cord. Receptacle center-to-center 1½" (38mm) and 2" (51mm).
 J06B0B/J06B2B	6 rear outlets, lighted switch.	6' (1.8m) or 15' (4.6m) cord. Receptacle center-to-center 1½" (38mm).
 J06B0BX/J06B2BX	6 rear outlets.	6' (1.8m) or 15' (4.6m) cord. Receptacle center-center 1½" (38mm).
 J60B0B/J60B2B	6 front outlets, lighted switch.	6' (1.8m) or 15' (4.6m) cord. Receptacle center-to-center 1½" (38mm).
 J60B0B-90/J60B0B-90	6 15 Amp front outlets. Receptacles rotated 90°.	6' (1.8m) or 15' (4.6m) cord. Receptacle center-to-center 1½" (38mm).
 J24B0B/J24B2B	2 15 Amp front, 4 rear outlets. Lighted switch.	6' (1.8m) or 15' (4.6m) cord. Receptacle center-to-center 1½" (38mm).

20 Amp Rackmount Plug-In Outlets

Model	Description/Specifications	Dimensions
 J06B0B20/J06B2B20	6 rear outlets, lighted switch.	6' (1.8m) or 15' (4.6m) cord. Receptacle center-to-center 1½" (38mm).
 J06B0B20X/J06B2B20X	6 rear outlets.	6' (1.8m) or 15' (4.6m) cord. Receptacle center-to-center 1½" (38mm).
 J60B0B20/J60B2B20	6 front outlets, lighted switch.	6' (1.8m) or 15' (4.6m) cord. Receptacle center-to-center 1½" (38mm).
 J60B0B20X/J60B2B20X	6 front outlets.	6' (1.8m) or 15' (4.6m) cord. Receptacle center-center 1½" (38mm).