

Selection Guide by Feature – Majortel Power Systems

Feature System #	DC Output Capacity		AC Input		RU	Power Module			DC Output		
	Total Amps	Total Watts	Terminal Block – H/W	Line Cord—6ft NEMA	19" x rack U height	MTR48/15-1U	MTR48/25-1U	MTR130/10-1U	Fixed - battery	Fixed - load	Field Config -load
MTS48/30FL-1U	30	1740	②		①	②			①		⑩*
MTS48/30BL-1U	30	1740	②		①	②			①		④
MTS48/50AT-1U	50	2900	①		①		②		①	①	
MTS48/50AT-2U	50	2900	②		②		②		①	②	④
MTS48/75AT-2U	75	4350	②		②		③		①	②	④
MTS48/100AT-2U	100	5800	②		②		④		①	②	④
MTS130/20AT-1U	20	2800	①		①			②	①#		
MTS130/10AT-1U	10	1400	①		①			①	①#		
DC-DC Converters											
			130 VDC Input			MTDC (25A) – 1U					
MTD48/25-130-1U	25	1450	①		①		①				②
MTD48/50-130-1U	50	2900	①		①		②				②
MTD24/25-130-1U	25	800	①		①		①				②
MTD24/50-130-1U	50	1600	①		①		②				②

note: The symbol [①] is used to indicate the quantity of a part or component element in a system.

* - FL system supports GMT fuses only
- 130V system is 2-pole circuit breaker

“Field Configurable” circuit breakers available in 5, 10, 15, 20, 30 amp ratings